

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Previously Presented) A position indication device for indicating a position within a screen of a display device, the position indication device comprising:
  - an indicator body that indicates a position within a screen of a display device;
  - a lens that is provided in the indicator body and focuses light that is incident from a position indicated by the indicator body through a light-incident aperture of the indicator body;
  - an optical sensor that is provided in the indicator body and detects light focused by the lens; and
  - a light-proof member that is provided in the indicator body and covers the lens and the optical sensor completely in such a manner that external light other than light from the light-incident aperture is not incident on the lens and the optical sensor.
2. (Original) The position indication device as defined by claim 1,
  - wherein the light-proof member covers the optical sensor in such a manner as to prevent the incidence of external light to all surfaces of the optical sensor, including a surface on which a signal terminal of the optical sensor is provided.
3. (Original) The position indication device as defined by claim 1,
  - wherein the light-proof member covers at least a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor.
4. (Original) The position indication device as defined by claim 2,
  - wherein the light-proof member covers at least a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor.

5. (Previously Presented) A position indication device for indicating a position within a screen of a display device, the position indication device comprising:
- an indicator body that indicates a position within a screen of a display device;
  - a lens that is provided in the indicator body and focuses light that is incident from a position indicated by the indicator body through a light-incident aperture of the indicator body;
  - an optical sensor that is provided in the indicator body and detects light focused by the lens; and
  - a light-proof member that is provided in the indicator body and covers the lens and the optical sensor in such a manner that external light other than light from the light-incident aperture is not incident on the lens and the optical sensor, wherein:
    - the light-proof member is configured of an assembly of a plurality of parts; and
    - a cut-out portion is provided in a connection portion between parts of the light-proof member, in order to form a through-hole for a signal terminal of the optical sensor.
6. (Original) The position indication device as defined by claim 2, wherein:
- the light-proof member is configured of an assembly of a plurality of parts; and
  - a cut-out portion is provided in a connection portion between parts of the light-proof member, in order to form a through-hole for the signal terminal of the optical sensor.
7. (Original) The position indication device as defined by claim 3, wherein:
- the light-proof member is configured of an assembly of a plurality of parts; and
  - a cut-out portion is provided in a connection portion between parts of the light-proof member, in order to form a through-hole for a signal terminal of the optical sensor.
8. (Original) The position indication device as defined by claim 1, wherein:
- the light-proof member is configured of an assembly of a plurality of parts; and

a protuberant portion is provided in a connection portion of a first part of the plurality of parts, and also a fit portion that fits with the protuberant portion is provided in a connection portion of a second part of the plurality of parts.

9. (Original) The position indication device as defined by claim 2, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

a protuberant portion is provided in a connection portion of a first part of the plurality of parts, and also a fit portion that fits with the protuberant portion is provided in a connection portion of a second part of the plurality of parts.

10. (Original) The position indication device as defined by claim 3, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

a protuberant portion is provided in a connection portion of a first part of the plurality of parts, and also a fit portion that fits with the protuberant portion is provided in a connection portion of a second part of the plurality of parts.

11. (Original) The position indication device as defined by claim 5, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

a protuberant portion is provided in a connection portion of a first part of the plurality of parts, and also a fit portion that fits with the protuberant portion is provided in a connection portion of a second part of the plurality of parts.

12. (Previously Presented) A position indication device for indicating a position within a screen of a display device, the position indication device comprising:

an indicator body that indicates a position within a screen of a display device;

a lens that is provided in the indicator body and focuses light that is incident from a position indicated by the indicator body through a light-incident aperture of the indicator body;

an optical sensor that is provided in the indicator body and detects light focused by the lens; and

a light-proof member that is provided in the indicator body and covers the lens and the optical sensor in such a manner that external light other than light from the light-incident aperture is not incident on the lens and the optical sensor, wherein:

the light-proof member covers a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor; and

a second light-proof member is provided to prevent the incidence of the external light from a gap between the board and a slit provided in the light-proof member for the insertion of the board.

13. (Original) The position indication device as defined by claim 2, wherein:

the light-proof member covers a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor; and

a second light-proof member is provided to prevent the incidence of the external light from a gap between the board and a slit provided in the light-proof member for the insertion of the board.

14. (Original) The position indication device as defined by claim 3, wherein:

the light-proof member covers the board portion on which the optical sensor is mounted, of the board for mounting the optical sensor; and

a second light-proof member is provided to prevent the incidence of the external light from a gap between the board and a slit provided in the light-proof member for the insertion of the board.

15. (Original) The position indication device as defined by claim 5, wherein:

the light-proof member covers a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor; and

a second light-proof member is provided to prevent the incidence of the external light from a gap between the board and a slit provided in the light-proof member for the insertion of the board.

16. (Original) The position indication device as defined by claim 8, wherein:

the light-proof member covers a board portion on which the optical sensor is mounted, of a board for mounting the optical sensor; and

a second light-proof member is provided to prevent the incidence of the external light from a gap between the board and a slit provided in the light-proof member for the insertion of the board.

17. (Original) The position indication device as defined by claim 12, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

the second light-proof member is a protuberant portion that is deformed by the insertion of the board into the slit provided in each part of the light-proof member and seals the gap between the slit and the board.

18. (Original) The position indication device as defined by claim 13, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

the second light-proof member is a protuberant portion that is deformed by the insertion of the board into the slit provided in each part of the light-proof member and seals the gap between the slit and the board.

19. (Original) The position indication device as defined by claim 14, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and

the second light-proof member is a protuberant portion that is deformed by the insertion of the board into the slit provided in each part of the light-proof member and seals the gap between the slit and the board.

20. (Original) The position indication device as defined by claim 15, wherein:

the light-proof member is configured of an assembly of a plurality of parts; and  
the second light-proof member is a protuberant portion that is deformed by the  
insertion of the board into the slit provided in each part of the light-proof member and seals  
the gap between the slit and the board.

21. (Original) The position indication device as defined by claim 16, wherein:  
the light-proof member is configured of an assembly of a plurality of parts; and  
the second light-proof member is a protuberant portion that is deformed by the  
insertion of the board into the slit provided in each part of the light-proof member and seals  
the gap between the slit and the board.

22. (Previously Presented) A position indication device for indicating a position  
within a screen of a display device, the position indication device comprising:

an indicator body that indicates a position within a screen of a display device;  
a lens that is provided in the indicator body and focuses light that is incident  
from a position indicated by the indicator body through a light-incident aperture of the  
indicator body;

an optical sensor that is provided in the indicator body and detects light  
focused by the lens; and

a light-proof member that is provided in the indicator body and covers the lens  
and the optical sensor in such a manner that external light other than light from the light-  
incident aperture is not incident on the lens and the optical sensor, wherein:

the light-proof member covers the entirety of a board on which the optical  
sensor is mounted; and

a second light-proof member is provided to prevent the incidence of external  
light from a gap between a lead wire from the board and a lead hole provided in the light-  
proof member for the extraction of the lead wire.

23. (Previously Presented) A position indication device for indicating a position within a screen of a display device, the position indication device comprising:

an indicator body that indicates a position within a screen of a display device;

a lens that is provided in the indicator body and focuses light that is incident from a position indicated by the indicator body through a light-incident aperture of the indicator body;

an optical sensor that is provided in the indicator body and detects light focused by the lens; and

a light-proof member that is provided in the indicator body and covers the lens and the optical sensor in such a manner that external light other than light from the light-incident aperture is not incident on the lens and the optical sensor, wherein:

the optical sensor is installed directly within the light-proof member; and

a second light-proof member is provided to prevent the incidence of external light from a gap between a lead wire from a signal terminal of the optical sensor and a lead hole provided in the light-proof member for the extraction of the lead wire.

24. (Currently Amended) ~~A computer-usable information storage medium used in a game system~~ A game system that comprises:

a computer-usable information storage medium used in the game system;

the position indication device as defined by claim 1;

a game processing means-section that receives information from the position indication device and performs game processing based on the detected indicated position; and

an image generation means-section that generates a game image in accordance with the game processing performed by the game processing sectionmeans,

wherein the information storage medium comprises a program for implementing the above means-sections on a computer.

25. (Currently Amended) ~~A game system~~~~A computer usable information storage medium used in a game system~~ that comprises:

a computer-usable information storage medium used in the game system;  
the position indication device as defined by claim 5;  
a game processing ~~means~~section that receives information from the position indication device and performs game processing based on the detected indicated position; and  
an image generation ~~means~~section that generates a game image in accordance with the game processing performed by the game processing section~~means~~,  
wherein the information storage medium comprises a program for implementing the above ~~means~~sections on a computer.

26. (Currently Amended) ~~A game system~~~~A computer usable information storage medium used in a game system~~ that comprises:

a computer-usable information storage medium used in the game system;  
the position indication device as defined by claim 12;  
a game processing ~~means~~section that receives information from the position indication device and performs game processing based on the detected indicated position; and  
an image generation section ~~means~~ that generates a game image in accordance with the game processing performed by the game processing section~~means~~,  
wherein the information storage medium comprises a program for implementing the above sections ~~means~~ on a computer.

27. (Currently Amended) ~~A game system~~~~A computer usable information storage medium used in a game system~~ that comprises:

a computer-usable information storage medium used in the game system;  
the position indication device as defined by claim 22;



game processing section means-that receives information from the position indication device and performs game processing based on the detected indicated position; and

image generation section means-that generates a game image in accordance with the game processing performed by the game processing section means,

wherein the information storage medium comprises a program for implementing the above ~~means~~-sections on a computer.

28. (Currently Amended) A game system~~A computer usable information storage medium used in a game system~~ that comprises:

a computer-usable information storage medium used in the game system;

the position indication device as defined by claim 23;

game processing section means-that receives information from the position indication device and performs game processing based on the detected indicated position; and

image generation section means-that generates a game image in accordance with the game processing performed by the game processing section means,

wherein the information storage medium comprises a program for implementing the above ~~means~~-sections on a computer.